HS-AS Studs
glue face

Glue face studs are designed to provide a stronger glue surface to connect an accelerometer to the machine.

Mounting Studs provide a secure, permanent or semi-permanent point of connection

Part No.	Connection Point 1	Connection Point 2		
HS-AS014	¼”-28 UNF Male	Glue Face x Ø19mm		
HS-AS019-15	Magnet	Glue Face x Ø15mm		
HS-AS019-18	Magnet	Glue Face x Ø18mm		
HS-AS019-24	Magnet	Glue Face x Ø24mm		For quantity this product can be etched
HS-AS019-30	Magnet	Glue Face x Ø30mm		For quantity this product can be etched
HS-AS019-38	Magnet	Glue Face x Ø38mm		For quantity this product can be etched
HS-AS027-M6	M6 Female	Glue Face x 20mm AF		
HS-AS027-M8	M8 Female	Glue Face x 20mm AF		
HS-AS027-M8x1	M8 x 1 Female	Glue Face x 20mm AF		
HS-AS027-1/4	1/4"-28UNF Hex Female	Glue Face x 20mm AF		
HS-AS029	10-32 UNF Male	Glue Face x Ø19mm		
HS-AS036	M8 Male	Glue Face x 20.6mm AF		

Hansford Sensors
Excellence in Vibration Monitoring

www.hansfordsensors.com
sales@hansfordsensors.com

We reserve the right to alter the specification of this product without prior notice

HS-AS Studs

glue face

Part No.	Connection Point 1	Connection Point 2
HS-AS059-1/4	¼”-28 UNF Female	Glue Face x Ø19mm
HS-AS059-1/4-25	¼”-28 UNF Female	Glue Face x Ø25mm
HS-AS059-1/4-30	¼”-28 UNF Female	Glue Face x Ø30mm
HS-AS059-M6	M6 Female	Glue Face x Ø19mm
HS-AS059-M8	M8 x 1.25 Female	Glue Face x Ø19mm
HS-AS087	Magnet - Ø5mm Centre Hole	Glue Face x Ø19mm

Hansford Sensors
Excellence in Vibration Monitoring

www.hansfordsensors.com
sales@hansfordsensors.com

We reserve the right to alter the specification of this product without prior notice